

ストレートスプリング								
バネ内径	自由長	レート (kg/mm)	製品番号	本体価格 (税抜)	最大許容ストローク (mm)	最大許容荷重 (kgf)	単体重量 (g)	
65mm	150mm	4.0	P65/4K150	¥7,000	94	376	670	
		5.0	P65/5K150	¥6,500	82	410	890	
		6.0	P65/6K150	¥8,500	86	519	820	
		7.0	P65/7K150	¥7,500	84	589	930	
		8.0	P65/8K150	¥8,500	84	675	1,050	
	10.0	P65/10K150	¥7,500	75	752	1,110		
	160mm	4.0	P65/4K160	¥7,000	97	389	670	
		6.0	P65/6K160	¥7,000	96	591	1,020	
		8.0	P65/8K160	¥7,500	96	771	1,050	
		10.0	P65/10K160	¥8,000	85	851	1,350	
	170mm	3.0	P65/3K170	¥7,000	111	333	630	
		4.0	P65/4K170	¥7,000	103	414	860	
		5.0	P65/5K170	¥7,500	103	520	930	
		6.0	P65/6K170	¥8,000	98	590	1,040	
		7.0	P65/7K170	¥8,000	96	672	1,160	
		8.0	P65/8K170	¥8,000	94	753	1,300	
		10.0	P65/10K170	¥8,000	84	850	1,340	
	180mm	4.0	P65/4K180	¥7,500	113	453	870	
		5.0	P65/5K180	¥7,000	104	521	940	
		6.0	P65/6K180	¥7,500	99	595	1,040	
		8.0	P65/8K180	¥8,500	95	760	1,290	
		16.0	P65/16K180	¥13,000	79	1,266	1,980	
		20.0	P65/20K180	¥13,000	70	1,402	1,990	
	190mm	22.0	P65/22K180	¥14,000	69	1,518	2,180	
		3.0	P65/3K190	¥7,000	123	390	790	
		4.0	P65/4K190	¥7,000	112	451	870	
		5.0	P65/5K190	¥8,000	110	550	1,190	
		6.0	P65/6K190	¥8,000	107	642	1,300	
		8.0	P65/8K190	¥8,000	99	795	1,590	
		10.0	P65/10K190	¥8,500	94	945	1,630	
		12.0	P65/12K190	¥9,000	87	1,048	1,720	
		14.0	P65/14K190	¥11,000	83	1,165	1,840	
		18.0	P65/18K190	¥15,000	77	1,388	2,150	
		20.0	P65/20K190	¥15,000	76	1,521	2,330	
		22.0	P65/22K190	¥16,000	72	1,671	2,440	
	195mm	24.0	P65/24K190	¥15,000	69	1,658	2,380	
		4.5	P65/4.5K195	¥7,500	116	518	1,020	
		200mm	6.0	P65/6K200	¥8,000	112	672	1,300
			8.0	P65/8K200	¥8,000	106	851	1,590
			10.0	P65/10K200	¥8,500	94	945	1,630
			14.0	P65/14K200	¥9,800	83	1,160	1,840
		16.0	P65/16K200	¥9,800	79	1,270	1,980	
		18.0	P65/18K200	¥16,000	85	1,530	2,520	
		20.0	P65/20K200	¥17,000	83	1,660	2,720	
		22.0	P65/22K200	¥16,000	75	1,652	2,540	
	24.0	P65/24K200	¥17,000	75	1,802	2,760		
	210mm	4.0	P65/4K210	¥7,500	129	518	1,120	
		5.0	P65/5K210	¥7,500	118	591	1,190	
		6.0	P65/6K210	¥8,000	112	672	1,300	
		8.0	P65/8K210	¥8,500	106	848	1,590	
		10.0	P65/10K210	¥8,500	94	945	1,630	
		12.0	P65/12K210	¥11,000	96	1,157	2,060	
		14.0	P65/14K210	¥11,000	91	1,277	2,190	
		22.0	P65/22K210	¥18,000	82	1,805	2,950	
	220mm	6.0	P65/6K220	¥8,000	123	738	1,610	
		8.0	P65/8K220	¥8,000	106	852	1,590	
		10.0	P65/10K220	¥10,000	105	1,051	1,980	
		12.0	P65/12K220	¥12,000	104	1,248	2,470	
		16.0	P65/16K220	¥15,000	87	1,392	2,340	
		18.0	P65/18K220	¥16,000	85	1,530	2,520	
		20.0	P65/20K220	¥20,000	83	1,660	2,730	
		22.0	P65/22K220	¥18,000	82	1,805	2,950	
		24.0	P65/24K220	¥20,000	81	1,944	3,200	
		25.0	P65/25K220	¥20,000	78	1,949	3,110	
		26.0	P65/26K220	¥19,000	75	1,950	3,020	
		27.0	P65/27K220	¥19,000	72	1,944	2,930	
	230mm	4.0	P65/4K230	¥7,500	130	521	1,110	
		6.0	P65/6K230	¥9,000	126	760	1,610	
		7.0	P65/7K230	¥9,000	121	848	1,770	
		8.0	P65/8K230	¥9,500	118	949	1,940	
		10.0	P65/10K230	¥10,000	105	1,051	1,980	
	6inch (152mm)	10.0	P65/10K6IN	¥7,000	75	752	1,110	
	6.5inch (165mm)	12.0	P65/12K6.5IN	¥8,500	79	950	1,430	
	7inch (178mm)	10.0	P65/10K7IN	¥8,000	85	851	1,350	
		14.0	P65/14K7IN	¥9,500	75	1,052	1,540	
	8inch (203mm)	10.0	P65/10K8IN	¥9,500	94	945	1,630	
		12.0	P65/12K8IN	¥8,500	96	1,155	2,060	

ストレートスプリング							
バネ内径	自由長	レート (kg/mm)	製品番号	本体価格 (税抜)	最大許容ストローク (mm)	最大許容荷重 (kgf)	単体重量 (g)
70mm	140mm	8.0	P70/8K140	¥8,000	80	640	990
		5.0	P70/5K140	¥7,500	90	450	880
	150mm	6.0	P70/6K150	¥7,500	88	528	970
		8.0	P70/8K150	¥8,000	81	649	1,210
		10.0	P70/10K150	¥8,000	78	807	1,230
		6.0	P70/6K160	¥7,000	94	564	970
	160mm	7.0	P70/7K160	¥8,500	91	638	1,080
		8.0	P70/8K160	¥9,000	90	720	1,210
		14.0	P70/14K160	¥11,000	79	1,106	1,710
		4.0	P70/4K170	¥7,000	107	428	810
	170mm	5.0	P70/5K170	¥8,500	100	501	1,100
		6.0	P70/6K170	¥8,000	98	589	1,200
		7.0	P70/7K170	¥9,500	94	658	1,330
		8.0	P70/8K170	¥8,000	91	728	1,470
		10.0	P70/10K170	¥10,000	90	902	1,520
		12.0	P70/12K170	¥10,000	83	996	1,610
		16.0	P70/16K170	¥12,000	76	1,216	1,850
		4.0	P70/4K180	¥8,000	111	444	1,030
	180mm	5.0	P70/5K180	¥9,000	110	551	1,100
		10.0	P70/10K180	¥11,000	91	911	1,830
		12.0	P70/12K180	¥12,000	92	1,104	1,910
		5.0	P70/5K190	¥8,500	112	561	1,100
	190mm	6.0	P70/6K190	¥7,500	106	637	1,200
		8.0	P70/8K190	¥8,500	101	811	1,470
		10.0	P70/10K190	¥9,500	100	999	1,830
		12.0	P70/12K190	¥12,000	92	1,104	1,920
	200mm	4.0	P70/4K200	¥8,000	123	492	1,030
		5.0	P70/5K200	¥8,500	118	591	1,370
		6.0	P70/6K200	¥8,500	116	694	1,490
		8.0	P70/8K200	¥9,000	101	809	1,470
	220mm	10.0	P70/10K200	¥9,500	99	995	1,820
		6.0	P70/6K220	¥9,000	122	792	1,730
	4.5inch (114mm)	8.0	P70/8K220	¥9,000	113	904	1,790
		12.0	P70/12K4.5IN	¥7,000	59	706	930
	5inch (127mm)	12.0	P70/12K5IN	¥8,000	64	767	1,120
		12.0	P70/12K6IN	¥9,000	75	900	1,340
	6inch (152mm)	14.0	P70/14K6IN	¥11,000	71	994	1,710

バレルフォルム(タル型)スプリング							
バネ内径	自由長	レート (kg/mm)	製品番号	本体価格 (税抜)	最大許容ストローク (mm)	最大許容荷重 (kgf)	単体重量 (g)
65mm	160mm	4.0	P65/4K160W	¥10,000	104	416	920
		4.0	P65/4K170W	¥11,000	103	412	1,160
	170mm	5.0	P65/5K170W	¥10,000	95	475	1,380
		3.0	P65/3K175W	¥8,500	119	357	870
	180mm	3.0	P65/3K180W	¥9,000	113	339	1,120
		4.0	P65/4K180W	¥10,000	113	452	1,160
		5.0	P65/5K180W	¥10,000	105	525	1,390
	185mm	3.0	P65/3K185W	¥8,500	117	351	1,120
		3.0	P65/3K190W	¥9,000	123	369	1,120
	190mm	4.0	P65/4K190W	¥9,500	124	492	1,160
		5.0	P65/5K190W	¥14,000	124	620	1,390
	200mm	3.0	P65/3K200W	¥10,000	133	399	1,110
		4.0	P65/4K200W	¥9,000	136	544	1,300
	210mm	4.0	P65/4K210W	¥11,000	133	532	1,620
		5.0	P65/5K210W	¥12,000	133	665	1,710
	220mm	5.0	P65/5K220W	¥12,500	140	700	1,710
		160mm	4.0	P70/4K160W	¥8,000	107	428
	170mm		6.0	P70/6K170W	¥12,000	101	606
		175mm	3.0	P70/3K175W	¥8,000	119	357
	180mm		5.0	P70/5K180W	¥10,000	117	585
190mm		4.0	P70/4K190W	¥8,500	117	468	1,300
	6.0	P70/6K190W	¥13,000	114	684	2,000	
200mm		3.0	P70/3K200W	¥8,000	128	386	1,060
	4.0	P70/4K200W	¥8,500	127	508	1,300	
	5.0	P70/5K200W	¥13,000	123	615	1,710	
210mm	3.0	P70/3K210W	¥8,000	138	416	1,060	
	4.0	P70/4K210W	¥15,000	134	536	1,620	
	5.0	P70/5K210W	¥15,000	133	665	1,710	
220mm	6.0	P70/6K210W	¥15,000	134	804	2,000	
	5.0	P70/5K220W	¥13,500	140	700	1,710	
230mm	5.0	P70/5K230W	¥15,000	144	720	2,280	
	6.0	P70/6K230W	¥15,000	142	852	2,410	



注意
メインスプリングの密着(全圧着)までのご使用は、本来のバネ性能が損なわれるだけでなく、ヘタリ、変形、折損する恐れがございますので、上記の最大許容ストローク及び最大許容荷重の範囲内でご使用ください。

